



Network Video Recorder

Quick Operation Guide

UD.6L0202B1119A01

Thank you for purchasing our product. If there is any question or request, please do not hesitate to contact dealer. This manual is applicable to the models listed in the following table.

Series	Model	Type
7100NI-SL	DS-7104NI-SL	Network Video Recorder
	DS-7108NI-SL	

NVR Pre-Installation

The DS-7100NI-SL series NVR are highly advanced surveillance equipment that should be installed with care. Please take into consideration the following precautionary steps before installation of the NVR.

1. Keep all liquids away from the NVR.
2. Install the NVR in a well-ventilated and dust-free area.
3. Ensure environmental conditions meet factory specifications.
4. Install a manufacturer recommended HDD.

NVR Installation

During the installation of the NVR:

1. Use brackets for rack mounting.
2. Ensure there is ample room for audio and video cables.
3. When installing cables, ensure that the bend radius of the cables are no less than five times than its diameter.
4. Connect both the alarm and RS-485 cable.
5. Allow at least 2cm (≈0.75-inch) of space between racks mounted devices.
6. Ensure the NVR is grounded.
7. Environmental temperature should be within the range of -10 °C ~ 55 °C, 14 °F ~ 131 °F.
8. Environmental humidity should be within the range of 10% ~ 90%.

Hard Disk Installation

Before you start:


Before installing a hard disk drive (HDD), please make sure the power is disconnected from the NVR. A factory recommended HDD should be used for this installation.

1 SATA hard disks can be installed on your NVR.


Tools Required: Screwdriver.

Steps:


1. Remove the cover from the NVR by unfastening the screws on the bottom.



2. Place the HDD on the bottom of the device and then fasten the screws on the bottom to fix the HDD.




3. Connect one end of the data cable to the motherboard of NVR and the other end to the HDD.
4. Connect the power cable to the HDD.






5. Re-install the cover of the NVR and fasten screws.

Front Panel


The front panel of DS-7100NI-SL is shown below:



No.	Icon	Description
1		Indicator turns red when DVR is powered up.
2		Indicator lights in red when data is being read from or written to HDD.
3		Indicator blinks blue when network connection is functioning properly.

Rear Panel

The rear panel of DS-7100NI-SL is shown below:



No.	Item	Description
1	Power Supply	12VDC power supply.
2	Audio In	RCA connector for voice talk input.
3	HDMI Interface	HDMI video output connector.
4	LAN Network Interface	Connector for LAN (Local Area Network).
5	Audio Out	RCA connector for audio output.
6	VGA Output	DB9 connector for VGA output. Display local video output and menu.
7	USB Interface	Universal Serial Bus (USB) ports for additional devices such as USB mouse and USB Hard Disk Drive (HDD).

Specifications

Specifications of DS-7100NI-SL

Model		DS-7104NI-SL	DS-7108NI-SL
Video/Audio input	IP video input	4-ch	8-ch
	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)	
Network	Incoming bandwidth	20Mbps	40Mbps
	Outgoing bandwidth	40Mbps	
	Remote connection	128	
Video/Audio output	Recording resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz	
	Audio output	1-ch, RCA (Linear, 1kΩ)	
	Playback resolution	5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF	
	Synchronous playback	4-ch@720P / 2-ch@1080P / 1-ch@5MP	8-ch@4CIF /4-ch@720P / 2-ch@1080P / 1-ch@5MP
Hard disk	SATA	1 SATA interface for 1 HDD	
	Capacity	Up to 4TB for each disk	
External interface	Network interface	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface	
	USB interface	2 × USB 2.0	
Others	Power supply	12VDC	
	Consumption	≤ 15 W (without hard disk)	
	Working temperature	-10 ℃ ~ +55 ℃	
	Working humidity	10 % ~ 90 %	
	Chassis	1U chassis	
	Dimensions (W × D × H)	200 × 200 × 45 mm	
	Weight	≤ 1 Kg (without hard disk)	

HDD Storage Calculation Chart

The following chart shows an estimation of storage space used based on recording at one channel for an hour at a fixed bit rate.


Bit Rate	Storage Used
96K	42M
128K	56M
160K	70M
192K	84M
224K	98M
256K	112M
320K	140M
384K	168M
448K	196M
512K	225M
640K	281M
768K	337M
896K	393M
1024K	450M
1280K	562M
1536K	675M
1792K	787M
2048K	900M
4096K	1800M
8192K	3600M
16384K	7200M

Note: Please note that supplied values for storage space used is just for reference. Storage space used is estimated by formulas and may have some deviation from actual value.

Accessing by Web Browser

Logging In

You can get access to the device via web browser. Open web browser, input the IP address of the device and then press Enter. The login interface appears.



Input the user name and password, and click the Login button.

Notes:

1. The default IP address is 192.0.0.64.
2. The default user name is admin, and password is 12345.
3. You may use one of the following listed web browsers: Internet Explorer 6.0, Internet Explorer 7.0, Internet Explorer 8.0, Internet Explorer 9.0, Internet Explorer 10.0, Apple Safari, Mozilla Firefox, and Google Chrome.
4. The supported resolutions include 1024*768 and above.

When you log in for the first time, the system will remind you to install the Plug-in control. After the installation, you can configure and manage the device remotely.

Live View

The live view interface appears by default when you log in the device.



Interface Introduction


- ① Channel List: Displays the list of channels and the playing and recording status of each channel.
- ② Live View Window: Displays the image of channel, and multi-window division is supported.
- ③ Play Control Bar: Play control operations are supported.
- ④ PTZ Control: Pan, tilt, zoom operations are supported, as well as preset editing and calling.

Note: PTZ function can only be realized if the connected camera supports PTZ control.












- ⑤ Video Parameters Configuration: Brightness, contrast, saturation and hue of the image can be modified.

Start Live View

Steps:

1. In the live view window, select a playing window by clicking the mouse.
2. Double click a camera from the device list to start the live view.
3. You can click the  button on the toolbar to start the live view of all cameras on the device list.

Refer to the following table for the description of buttons on the live view window:

Icon	Description	Icon	Description
	Select the window-division mode		Start/Stop all live view
	Capture pictures in the live view mode		Start/Stop all recording
	Previous page		Next page
	Open/Close audio		Start/Stop two-way audio
	Adjust volume		Enable/Disable digital zoom
	Full-screen		

Recording


Before you start

Make sure the device is connected with HDD or network disk, and the HDD or network disk has been initialized for the first time to use.

Two recording types can be configured: Manual and Scheduled. The following section introduces the configuration of scheduled recording.

Steps:

1. Click Remote Configuration> Camera Settings> Record Schedule to enter Record Schedule settings interface.
2. Select the camera to configure the record schedule.
3. Check the checkbox of **Enable Schedule** to enable recording schedule.



4. Choose the day in a week to configure scheduled recording.
5. Click **Edit** to edit record schedule.

Period	Start Time	End Time	Record Type
1	00:00	24:00	Normal
2	00:00	00:00	Normal
3	00:00	00:00	Normal
4	00:00	00:00	Normal
5	00:00	00:00	Normal
6	00:00	00:00	Normal
7	00:00	00:00	Normal
8	00:00	00:00	Normal

- 1) Configure All Day or Customize record:

- If you want to configure the all-day recording, please check the **All Day** checkbox.
- If you want to record in different time sections, check the **Customize** checkbox. Set the **Start Time** and **End Time**.

Note: The time of each segment can't be overlapped. Up to 8 segments can be configured.

- 2) Select a **Record Type**. The record type can be Normal, Motion, Alarm, Motion & Alarm, and Motion | Alarm.
 - 3) Check the checkbox of **Select All** and click **Copy** to copy settings of this day to the whole week. You can also check any of the checkboxes before the date and click **Copy**.
 - 4) Click **OK** to save the settings and exit the **Edit Schedule** interface.
6. Click **Advanced** to configure advanced record parameters.
 7. Click **Save** to validate the above settings.

Playback














Interface Introduction

- ① Channel List: Displays the list of channels and the playing status of each channel.
- ② Playback Window: Displays the image of channel.
- ③ Play Control Bar: Play control operations are supported.
- ④ Time Line: Displays the time bar and the records marked with different colors.
- ⑤ Playback Status: Displays the playback status, including channel number and playback speed.
- ⑥ Calendar: You can select the date to play.



Start Playback

Steps:

1. Click **Playback** on the menu bar to enter playback interface.
2. Click the camera from the device list for playback.
3. Select the date from the calendar and click **Search**.
4. Click the **Play** button to play the video file searched on the current date.
5. Use the buttons on the toolbar to operate in playback mode.

Button	Description	Button	Description
	Play/Pause		Stop
	Slow down		Speed up
	Play by single frame		Capture
	Stop All Playback		Download
	Video Clip		Open/Close audio
	Full-screen		

6. You can drag the progress bar with the mouse to locate the exact playback point. You can also input the time

in the textbox : :  and click  button to locate the playback point.

The color of the video on the progress bar stands for the different video types.

 Command  Schedule Recording  Alarm Recording  Manual Recording

Log

You can view and export the log files at any time, including operation, alarm, exception and information of device.

Before you start

The Log function can be realized only when the device is connected with HDD or network disk. And make sure the HDD or network disk has been initialized for the first time to use.


Steps:

1. Click **Log** on the menu bar to enter the Log interface.

Live View Playback Log Configuration							admin Logout	
No.	Time	Major Type	Minor Type	Channel No.	Local/Remote User	Remote Host IP	Search Log	
1	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12	Major Type All Types Minor Type All Types Start Time 2013-02-28 00:00:00 End Time 2013-02-28 23:59:59 Q Search Save Log	
2	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
3	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
4	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
5	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
6	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
7	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
8	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
9	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
10	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
11	2013-02-28 09:38:38	Operation	Remote: Configure Parameters	A4	admin	192.168.1.12		
12	2013-02-28 09:38:38	Operation	Remote: Configure Parameters	A4	admin	192.168.1.12		
13	2013-02-28 09:38:38	Operation	Remote: Configure Parameters	A4	admin	192.168.1.12		
14	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
15	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
16	2013-02-28 09:38:38	Operation	Remote: Get Parameters		admin	192.168.1.12		
17	2013-02-28 09:38:39	Operation	Remote: Get Parameters		admin	192.168.1.12		
18	2013-02-28 09:38:40	Operation	Remote: Get Parameters		admin	192.168.1.12		
19	2013-02-28 09:38:41	Operation	Remote: Get Parameters		admin	192.168.1.12		
20	2013-02-28 09:38:41	Operation	Remote: Get Parameters		admin	192.168.1.12		
21	2013-02-28 09:38:41	Operation	Remote: Get Parameters		admin	192.168.1.12		
22	2013-02-28 09:38:42	Operation	Remote: Configure Parameters	A3	admin	192.168.1.12		
23	2013-02-28 09:38:42	Operation	Remote: Configure Parameters	A3	admin	192.168.1.12		
24	2013-02-28 09:38:42	Operation	Remote: Configure Parameters	A3	admin	192.168.1.12		
25	2013-02-28 09:38:42	Operation	Remote: Get Parameters		admin	192.168.1.12		
26	2013-02-28 09:38:42	Operation	Remote: Get Parameters		admin	192.168.1.12		
27	2013-02-28 09:38:42	Operation	Remote: Get Parameters		admin	192.168.1.12		
28	2013-02-28 09:38:42	Operation	Remote: Get Parameters		admin	192.168.1.12		
29	2013-02-28 09:38:47	Operation	Remote: Get Parameters		admin	192.168.1.12		
30	2013-02-28 09:38:47	Operation	Remote: Get Parameters		admin	192.168.1.12		
				Total 231 items			First Page Prev Page 1/7 Next Page Last Page	


- Set the log search conditions to refine your search, including the Major Type, Minor Type, Start Time and End Time.
- Click the **Search** button to start searching log files.
- The matched log files will be displayed on the list shown below.

Note: Up to 100 log files can be displayed each time.

You can click the  **Save Log** button to save the searched log files to local directory.

Menu Operation

Menu Structure



Startup and Shutdown

Proper startup and shutdown procedures are crucial to expanding the life of the NVR.


To start your NVR:

Check the power supply is plugged into an electrical outlet. It is **HIGHLY** recommended that an Uninterruptible Power Supply (UPS) be used in conjunction with the device. The Power indicator LED on the front panel should be red, indicating the device gets the power supply.

To shut down the NVR:

1. Enter the Shutdown menu.

Menu > Shutdown



2. Select the **Shutdown** button.
3. Click the **Yes** button.
4. Unplug the power supply when the shutdown attention pops up.

After the device starting up, the wizard will guide you through the initial settings, including modifying password, date and time settings, network settings, HDD initializing, and recording.

Live View

Some icons are provided on screen in Live View mode to indicate different camera status. These icons include:

Live View Icons

In the live view mode, there are icons at the right top of the screen for each channel, showing the status of the record and alarm in the channel, so that you can find problems as soon as possible.



Alarm (video loss, tampering, motion detection or sensor alarm).



Record (manual record, continuous record, motion detection or alarm triggered record)



Alarm & Record

Adding and Configuring IP Cameras


You should add and configure the online IP cameras to enable the live view and recording function.

Adding IP Cameras

You can search and add the online IP cameras by following the startup wizard, or according to the following steps.

Steps:

1. Right-click the mouse when you in the live view mode to show the right-click menu.
2. Select **Add IP Camera** in the pop-up menu and select **Auto** or **Manual** on your demand.



• Auto

The device will add the detected IP cameras or encoders automatically by the default user name and password of administrator.



Note: If the user name and password is changed, the auto adding of IP camera will be failed, you may add it


manually.

- **Manual**

Steps:








1. To add the online cameras with same network segment:

- 1) The detected online camera will be listed in the camera list, as shown in the figure below.




- 2) Click the  button to add the camera.

Explanation of the icons:

Icon	Explanation	Icon	Explanation
	Edit basic parameters of the camera		Add the detected IP camera.
	The camera is connected; you can click the icon to get the live view of the camera.		The camera is disconnected; you can click the icon to get the exception information of camera.
	The camera is connected.		Advanced settings of the camera.
	Delete the IP camera		

2. To add other IP cameras:

- 1) Click the **Custom Adding** button to pop up the Add IP Camera (Custom) interface.




- 2) You can edit the IP address, protocol, management port, and other information of the IP camera to be added.
- 3) Click **Add** to add the camera.

Configuring Basic Parameters of IP Cameras

After the adding of the IP cameras, the basic information of the camera lists in the page, and you can configure the

basic setting of the IP cameras.

Steps:

1. Click the  icon in the camera management interface to edit the parameters; you can edit the IP address, protocol and other parameters.



2. Click **OK** to save the settings and exit the editing interface.

Record Settings

Before you start:

Make sure that the HDD has already been installed. If not, please install a HDD and initialize it. You may refer to the user manual for detailed information.

Purpose:





Two kinds of record types are introduced in the following section, including Instant Record and All-day Record. And for other record types, you may refer to the user manual for detailed information.

Note: After rebooting all the manual records enabled are canceled.

Instant Record

On the live view window of each channel, there is a quick setting toolbar which shows on the bottom of the window when you click on it.




Click the  icon to enable the record, and the icon turns to . And click  icon to disable the record, then the icon turns to .

All-day Record

Perform the following steps to set the all-day recording.

On the live view window, right-click the window and move the cursor to the Start Recording option, and select Continuous Record or Motion Detection Record on your demand.




And click the **Yes** button in the popup Attention message box to confirm the settings. Then all the channels will start to record in the selected mode.

Playback

Play back the record files of a specific channel in the live view menu. Channel switch is supported.

Instant playback by channel

Choose a channel under live view using the mouse and click the  button in the shortcut operation menu.


Note: Only record files recorded during the past five minutes on this channel will be played back.



Playback by channel

Steps:

1. Enter the Playback menu.
Right-click a channel in live view mode and select Playback from the menu.



Under multi-screen live view, record files of the top left channel (not masked) will be played back.

2. Playback management.

The toolbar in the bottom part of Playback interface can be used to control playing process.



Just check the channel or channels if you want to switch playback to another channel or execute simultaneous playback of multiple channels.


Backup

Recorded files can be backed up to various devices, such as USB flash drives, USB HDDs or a DVD writer.

Steps:

1. Enter Video Export interface.

Choose the channel(s) you want to back up and click on the **Search** button.



2. Enter Export interface, choose backup device and click the **Export** button to start exporting.



3. Check backup result.

Choose the record file in Export interface and press button  to check it.

